



Tabulka specifikací

PLE/N eta	Označení	load capacity 1-leg 0° [kg]	load capacity 1-leg 90° [kg]	load capacity 2-leg 0° [kg]	load capacity 2-leg 90° [kg]	load capacity 2-leg 0°-45° [kg]	load capacity 2-leg 45°-60° [kg]	load capacity 3+4-leg 0°-45° [kg]	load capacity 3+4-leg 45°-60° [kg]	load capacity 2 asymm. [kg]	load capacity 3+4 asymm. [kg]
	PLE/N 6	1.120	1.120	2.240	2.240	1.500	1.120	2.300	1.600	1.120	1.120
	PLE/N 8	2.000	2.000	4.000	4.000	2.800	2.000	4.200	3.000	2.000	2.000
	PLE/N 10	3.150	3.150	6.300	6.300	4.400	3.150	6.600	4.700	3.150	3.150
	PLE/N 13	5.300	5.300	10.600	10.600	7.400	5.300	11.200	7.900	5.300	5.300
	PLE/N 16	8.000	8.000	16.000	16.000	11.300	8.000	16.900	12.000	8.000	8.000
	PLE/N 22	15.000	15.000	30.000	30.000	21.000	15.000	31.800	22.500	15.000	15.000

PLE/N eta	Označení	Nosnost [kg]	a [mm]	b [mm]	c [mm]	d [mm]	e [mm]	f [mm]	h [mm]	l [mm]	Hmotnost [kg/pc.]
	PLE/N 6	1.120	36	40	62	11	67	42	26	35	0,31
	PLE/N 8	2.000	37	42	69	13	73	45	28	37	0,40
	PLE/N 10	3.150	41	45	78	16,50	80	47	34	40	0,63
	PLE/N 13	5.300	61	55	99	22	97	53	44	50	1,46
	PLE/N 16	8.000	63	70	120	25	120	73	48	64	2,30
	PLE/N 22	15.000	89	97	163	33	163	92	70	90	5,40

Jistíci faktor 4

Upozornění: Technické změny vyhrazeny!