


Tabulka specifikací

ÜW Přechodové závěsy	Označení	Dvojitý hák DIN 15402	Nosnost [kg]	Složeno z	Hmotnost [kg/pc.]
	ÜW 50/4 II VSAW-HSWConnex	50	4.000	2xVSAW 1-16/AW36/CW16/HSW10	28,09
	ÜW 50/6,7 II VSAW-HW Connex	50	6.700	2xVSAW 1-16/AW36/CW16/HSW13	29,28
	ÜW 50/10 II VSAW- HW Connex	50	10.000	2xVSAW 1-16/AW36/CW16/HSW16	30,60
	ÜW 50/16 II VSAW-HS Connex	50	16.000	2xVSAW 1-16/AW36/CW19/20/HSW19/20	33,10
	ÜW 50/19 II VSAW-HS Connex	50	19.000	2xVSAW 1-22/AW50/CW26/HSW22	67,09
	ÜW 50/26,5 II VSAW-SW Connex	50	26.500	2xVSAW 1-22/AW50/CW26/HSW26	73,44
	ÜW 50/36 II VSAW-HS Connex	50	36.000	2xVSAW 1-22/AW50/CW32/HSW32	91,81
	ÜW 100/26,5 II VSAWHSW Connex	100	26.500	2xVSAW 1-32/320/AW50/CW26/HSW26	133,44
	ÜW 100/40 II VSAW-HW Connex	100	40.000	2xVSAW 1-32/320/AW50/CW32/HSW32	151,81

VSAW Úhel sklonu: max. 35°.