



# Tabulka specifikací

VMWP zvětšená 4 pramenná souprava	Označení	Složeno z	Nosnost 0°-45° [kg]	vhodné pro jednoduché háky dle. DIN 15401	vhodné pro dvojité háky dle. DIN 15402	Pro II-pramen	Pro III a IV-pramen
	VMWP - / 13	MWP 36 + 2 BWP 26	21.200	20	25	-	13
	VMWP - / 16	MWP 36 + 2 BWP 32	26.500	20	25	-	16
	VMWP 7/8	MWP 18 + 2 BWP 13	4.250	6	8	7 + 8	-
	VMWP 10/7/8	MWP 26 + 2 BWP 16	8.800	10	12	10	7 + 8
	VMWP 13/10	MWP 32 + 2 BWP 20	12.300	12	16	13	10

VMWP zvětšená 4 pramenná souprava	Označení	e [mm]	d [mm]	t [mm]	w [mm]	d1 [mm]	t1 [mm]	w1 [mm]	Hmotnost [kg/pc.]
	VMWP - / 13	415	38	275	150	27	140	65	11,50
	VMWP - / 16	425	38	275	150	33	150	70	13,80
	VMWP 7/8	214	19	160	95	13	54	25	1,47
	VMWP 10/7/8	260	27	190	110	17	70	34	3,45
	VMWP 13/10	315	33	230	130	20	85	40	6,28